**Part No: 9101** 



- Realtime presentation of Pore Pressure, Point Resistance, Friction etc
- Fully digital
- Standard cable can be used
- Dissipation tests of very long duration can be performed
- Innovative, easy to use, slot filter tip
- Automatic calibration and zero control



## Memocone corded mode

The probe operates with cable inside tubes giving real time readout. Manufacutred and calibrated in conformitiy with international standards. Automatic calibration and zero control before and after every test.

Pore water dissipation test included.

All our CPT probes are delivered with Inclinometer "tilt" as standard.

Delivered with the slot-filter point, porous filter available on request.

	Table of contents
1,2,3,5 or 10 ton CPT probe	1Pcs
Cable tube	1Pcs
30 meter cable	1Pcs
Grease cartridge	1Pcs
O-ring kit	1Pcs
Protection case	1Pcs
Calibration certificate	1Pcs

# Technical specification

### Point pressure

Accuracy: better than 0,01%FS Resolution: better than 0,003%FS

Net area factor: 0,68

#### Friction

Accuracy: better than 0,05%FS Resolution: better than 0,003%FS

Net area factor: 0,005

#### Pore pressure

Accuracy: better than 0,05%FS Resolution: better than 0,003%FS

Inclinometer +/- 20 grade

Produced, developed and manufactured in Sweden.

