**Part No: 9103** 



- All data stored in secure Flash memory during sounding
- Fully digital
- No cable through the rods needed during sounding
- · Data safely stored in Flash memory during sounding
- Innovative, easy to use, slot filter tip
- Automatic calibration and zero control



## Memocone cordless mode

The probe operates without cable, saving all results in the memory placed inside the probe itself. Manufactured and calibrated in conformity with international standards. Automatic calibration and zero control before and after test.

Pore water dissipation test included.

All our CPT probes are delivered with Inclinometer tilt as standard. Delivered with the slot-filter point, porous filter available on request.

	Table of contents
1,2,3,5 or 10 ton CPT probe	1Pcs
Battery tube	1Pcs
Battery plug	1Pcs
Grease cartridge	1Pcs
O-ring kit	1Pcs
Protection case	1Pcs
Calibration certificate	1Pcs

# Technical specification

## Point pressure

Accuracy: better than 0,01%FS Resolution: better than 0,003%FS

Net area factor: 0,68

#### Friction

Accuracy: better than 0,05%FS Resolution: better than 0,003%FS

Net area factor: 0,005

### Pore pressure

Accuracy: better than 0,05%FS Resolution: better than 0,003%FS

## **Inclinometer**

+/- 20 grade

Produced, developed and manufactured in Sweden.

