

MEMOCONE™ CABLE MODE

Part No: 9101



- Realtime presentation of:
 - Pore pressure (U_2)*
 - Point resistance (Q_c)*
 - Sleeve friction (F_s)*
 - Inclination*
 - Temperature*
- Fully digital
- Standard cable can be used
- Dissipation tests of very long duration can be performed
- Innovative, easy to use, slot filter tip

Memocone corded mode

The probe operates with cable inside tubes giving real time readout. Manufactured and calibrated in conformity with international standards. Automatic temperature compensation and parameter zero setting.

Pore water dissipation test included.

All our CPT probes are delivered with Inclinator tilt as standard.

Delivered with the slot-filter point, porous filter available on request.

Table of contents

5 or 10 ton CPT probe	1Pcs
Cable tube	1Pcs
30 meter cable	1Pcs
Communication cable 1,5 meters	1Pcs
Grease cartridge	1Pcs
20ml oil	1Pcs
O-ring kit	1Pcs
Protection case	1Pcs
Calibration certificate	1Pcs (Available online, printout upon request)

Technical specification

Point pressure

Accuracy: better than 0,01%FS

Resolution: better than 0,003%FS

Net area factor: 0,68

Friction

Accuracy: better than 0,05%FS

Resolution: better than 0,003%FS

Net area factor: 0,005

Pore pressure

Accuracy: better than 0,05%FS

Resolution: better than 0,003%FS

Inclinometer +/- 20 grade

Developed and manufactured in Sweden.

